

ML-8000



The ML-8000 is the latest addition to our industry-leading series of Monna Lisa digital textile printers. Equipped with eight newly developed PrecisionCore printheads, it packs the power and performance of world-class Epson inkjet printing and manufacturing technologies into an accessible entry-level package. Offering unprecedented performance and usability, it is a next-generation digital textile printer that will take your production capabilities to a new level.

High print quality and productivity

The ML-8000 boasts a typical print speed of 162 square metres per hour (2-pass printing at 600 x 600 dpi). Epson precision dot technologies include Microweave and lookup table (LUT) technologies that reduce banding and graininess, and advanced new Multi-Layer Halftone Technology (MLHT) that randomises the halftone dot pattern to reduce image degradation caused by dot misalignment. Dynamic Alignment Stabiliser (DAS) technology also ensures stable print quality by controlling waveforms on each printhead chip for higher dot placement accuracy and more uniform dot density on each pass. The ML-8000 also features symmetrical colour alignment for consistent colour overlap order during high-speed bidirectional printing, and Accurate Belt Position Control (ABPC) technology for precise fabric feeding. The result is optimal quality and speed, with superb reproduction of colour gradations, fine details, and complex geometric patterns.

Stable operation with minimal downtime

Stable operation and unprecedented usability are realised by advanced cleaning mechanisms and automated adjustment functions. A fluff blower system removes fluff from the fabric surface before it enters the printing area, and an ink mist extraction system helps reduce nozzle clogging problems. In the event a nozzle does become clogged, Nozzle Verification Technology (NVT) detects missing dots and adjusts ink delivery to maintain image quality and reduce printing errors. Auto nozzle cleaning by fabric wiper reduces daily manual maintenance work. With high-accuracy head alignment technology and automatic calibration by the built-in RGB camera, printhead replacement and calibration can be completed easily. In addition, the Epson Remote Monitoring System reduces downtime and service calls by allowing quick response to potential problems.

Easy operation

Ease of use is enhanced by a 9-inch LCD touch panel that displays current printer status, operating instructions, and regular maintenance procedures, and by hot-swappable, dual 10-litre or 3-litre high-capacity ink cartridges that allow uninterrupted production.


Environmentally friendly GENESTA Ink

Epson GENESTA inks are available in Acid, Reactive, Disperse, and Pigment formulations, and are ECO PASSPORT certified to meet globally recognised standards for environmentally friendly textile printing. Our Acid ink is also bluesign® approved, and our Reactive and Pigment inks are GOTS approved by ECOCERT.

Software for digital textile printing

Our original RIP software, Epson Edge Print Textile, has an intuitive interface for easy, 3-step, left-to-right operation, as well as step & repeat, hot folders, colour replacement for matching spot colours, and other convenient features. Optional ColorBlend preprocessing software also lets you create colour variations (colorways), control ink penetration to achieve visual equivalence on both sides of fabric, generate ICC profiles, and perform other preprocessing tasks.

Datasheet



Key features

Productivity

Maximum printing speed
312 sqm/h (300 x 600 dpi, 1 pass)*2
Typical printing speed
162 sqm/h (600 x 600 dpi, 2 pass)*3

High print quality

8 PrecisionCore Micro TFP printheads
Epson precision dot technology
Multi-Layer Halftone Technology (MLHT)
Dynamic Alignment Stabiliser (DAS) Technology
Symmetrical colour alignment
Accurate Belt Position Control (ABPC) Technology

Stable operation / Easy maintenance

Fluff blower system
Ink mist extraction system
Nozzle Verification Technology (NVT)
Auto nozzle cleaning by fabric wiper
Built-in RGB camera for auto calibration
Epson Cloud Solution PORT

Easy Operation

9-inch LCD touch panel
Dual 10-litre or 3-litre high-capacity ink cartridges

TECHNICAL SPECIFICATIONS

PRINT			
Printing technology	PrecisionCore inkjet technology		
Number of printheads	8		
Number of colours	8		
Maximum print resolution	1,200 x 1,200 dpi (Pigment), 1,200 x 600 dpi (Reactive, Acid, Disperse)		
Gradation process	Variable-Sized Droplet Technology		
Max print width	1,850 mm (72.8")		
Max print length	Unlimited		
Max fabric width	1,850 mm (72.8")		
Max fabric thickness	5.0 mm		
PRINT SPEED			
Square ^{*1}	Maximum printing speed (m ² /h)	312 (Reactive/Pigment)	279 (Acid/Disperse) (300x600 dpi, 1 pass) ^{*2}
	Typical printing speed 1 (m ² /h)	162 (Reactive/Pigment)	144 (Acid/Disperse) (600x600 dpi, 2 pass) ^{*3}
	Typical printing speed 2 (m ² /h)	108 (Reactive/Pigment)	96 (Acid/Disperse) (900x600 dpi, 3 pass) ^{*4}
	Maximum printing speed (sq ft/hr)	3,358 (Reactive/Pigment)	3,003 (Acid/Disperse) (300x600 dpi, 1 pass) ^{*2}
	Typical printing speed 1 (sq ft/hr)	1,744 (Reactive/Pigment)	1,550 (Acid/Disperse) (600x600 dpi, 2 pass) ^{*3}
	Typical printing speed 2 (sq ft/hr)	1,163 (Reactive/Pigment)	1,033 (Acid/Disperse) (900x600 dpi, 3 pass) ^{*4}
Linear ^{*1}	Maximum printing speed (lmt/h)	208 (Reactive/Pigment)	186 (Acid/Disperse) (300x600 dpi, 1 pass) ^{*2}
	Typical printing speed 1 (lmt/h)	108 (Reactive/Pigment)	96 (Acid/Disperse) (600x600 dpi, 2 pass) ^{*3}
	Typical printing speed 2 (lmt/h)	72 (Reactive/Pigment)	64 (Acid/Disperse) (900x600 dpi, 3 pass) ^{*4}
	Maximum printing speed (li ft/hr)	682 (Reactive/Pigment)	610 (Acid/Disperse) (300x600 dpi, 1 pass) ^{*2}
	Typical printing speed 1 (li ft/hr)	354 (Reactive/Pigment)	315 (Acid/Disperse) (600x600 dpi, 2 pass) ^{*3}
	Typical printing speed 2 (li ft/hr)	236 (Reactive/Pigment)	210 (Acid/Disperse) (900x600 dpi, 3 pass) ^{*4}
FABRIC HANDLING			
Fabric drive	Conveyor belt with thermoplastic adhesive		
Belt washing	Automatic		
STANDARD FEEDER			
Fabric roll diameter	400 mm (15.7")		
Fabric roll weight	100 kg (220 lb)		
Fabric roll core diameter	2" or 3"		
ENVIRONMENTAL CHARACTERISTICS			
Temperature	Operating: 20°C - 30°C (68°F - 86°F), Recommended: 22°C - 28°C (72°F - 82°F)		
Humidity	Operating: 40 - 60%RH (no condensation)		
ELECTRICAL			
Voltage	Main unit: 380-415 V, 3 phase + Neutral + Earth, 50Hz/60Hz		
Rated current	Main unit: 20 A		
Power consumption (Operating)	Main unit: 5.5 kW		
CERTIFICATIONS			
Safety	Canada: CAN/CSA-C22.2 No.301 Industrial electrical machinery,CAN/CSA C22.2 No.0, ICES-003 Class A U.S.A: UL 2011 (Outline of Investigation for Machinery), NFPA 79 (Electrical Standard for Industrial Machinery), FCC Part15 Subpart B, Class A Mexico: NOM-019-SCFI-1998 *check HS Code Brazil: NR12 Safety in Machinery and Equipment Work EU,EFTAcountries,Turkey: Machinery Directive 2006/42/EC AnnexI, IEC/EN 60204-1, EN ISO12100, EN ISO11111-1, EN ISO13849-1, EN 55011, EN 61000-6-2, EN 61000-6-4 Morocco: Order No.2573-14,Order No.2574-14 Russia,Belarus,Kazakhstan: ISO 12100, ISO 13849-1, IEC/EN 60204-1, EN ISO 11111-1, EN 55011, EN 61000-6-2, EN 61000-6-4, EN 62311 Ukraine: ISO 12100, ISO 13849-1, IEC/EN 60204-1, EN ISO 11111-1, EN 55011, EN 61000-6-2, EN 61000-6-4 Australia,Newzealand: AS CISPR11 India: IS13252(Part 1) Uzbekistan: Safety and EMC(CE), Factory Audit Jordan: Safety and EMC(CE) Saudi Arabia: Safety and EMC(CE) UAE: Safety and RoHS(CE), Factory Audit Sri Lanka: safety and EMC(CE) Korea: Korean MSIP regulation KN11, KN61000-6-2		
Electromagnetic	Korea: Korean MSIP regulation KN11, KN61000-6-2		
NETWORK			
Transmission speed	USB3.0 Ethernet 1000BASE-T		

^{*1} Printing width: 1500mm, Printing mode: bidirectional. Printing speeds vary depending on such factors as image printed, firmware version, operating state of PC and print settings.

^{*2} At 300 x 300 dpi with 2 halftone layers

^{*3} At 300 x 300 dpi with 4 halftone layers

^{*4} At 300 x 300 dpi with 6 halftone layers

ML-8000 & Working Area Dimensions



GENESTA INK

- **Acid**
Black, Cyan, Magenta, Yellow, Grey, Red, Blue, Cobalt, Orange, Rubine, Fluorescent Pink, Fluorescent Flavine, ACROSS (Ink penetration liquid)
- **Reactive**
Black, Cyan, Magenta, Yellow, Grey, Red, Blue, Orange, Crimson, ACROSS (Ink penetration liquid)
- **Disperse**
Black, Cyan, Magenta, Yellow, Grey, Red, Blue, Orange, ACROSS (Ink penetration liquid)
- **Pigment**
Black, Cyan, Magenta, Yellow, Grey, Red, Green, Orange
- **Ink capacity**
10 litres, 3 litres

DIMENSIONS

- **Printer**
3,700 (W) x 2,690 (D) x 1,830 (H) mm
(146 x 106 x 72 in)
- **Ink rack (with 10L ink)**
880 (W) x 960 (D) x 790 (H) mm
(35 x 38 x 31 in)

WEIGHT

- **Printer**
Approx. 2,150 kg (4,740 lb)
- **Ink rack**
Approx. 110 kg (243 lb, not including ink)