

# Epson Monna Lisa Evo Tre 8



Monna Lisa Evo Tre is an industrial digital textile printer based on Total Solution, the fully integrated system where all components belong to the same process to guarantee the best printing results and the utmost customer satisfaction. This is the result of the synergy of Epson inkjet printing technology with engineering by F.lli Robustelli and pre/post-treatment and inks by For.Text, both companies now part of the Epson Group.

## Excellence and productivity in digital textile printing

The high quality and productivity of Monna Lisa Evo Tre derives from Epson's advanced PrecisionCore 4-chip print heads. Symmetric heads ensure consistent bi-directional printing, improving both print quality and productivity. Optimized Variable-sized Droplet technology guarantees extreme accuracy in reproducing nuances and very detailed or geometric patterns, as well as the best quality/speed ratio. Productivity is further increased by easy maintenance and minimized downtime.

## Flexibility to meet any printing need

Epson's inkjet printing technology is characterized by the flexibility to print on a wide range of media. This is also true for Direct-to-Fabric printing. With the Monna Lisa Evo Tre you have a single printer that meets a variety of different production needs and applications, as it can print on any type of fabric by installing the corresponding ink types. Flexibility also means a full range of configurations by number of print heads (8 in this case, upgradable to 16 heads at the factory) and printing widths (up to 220 cm).



## Easy ink management

Genesta is the family of inks specifically designed for the Monna Lisa Evo Tre series. It is available in four different types according to fabric or application: Acid, Reactive, Disperse and Pigment. The exclusive vacuum-packed degassed ink management system is designed to obtain the maximum efficiency while minimizing ink waste. Colour ink racks are available in different capacities (3 L as standard, 10 L optional).

## Epson Edge Print Textile

Quality, productivity and versatility is further enhanced by software specifically designed to get the most out of your Monna Lisa Evo Tre. The freedom to use other RIPs or textile CADs is one of the printer's main flexibility features.

## Datasheet



## Key features

### High quality and productivity

Configuration with 8 PrecisionCore Micro TFP print heads, upgradable to 16 heads at the factory

### Maximum printing speed

234 sqm/h (156 Lmt/h) (300x600 dpi, 1 pass)

### Ink management

Acid, Reactive, Disperse and Pigment inks in different capacities (3 L as standard, 10 L optional)

### Extensive software compatibility

Epson Edge Print Textile for Monna Lisa Evo Tre and the flexibility to use other RIPs or textile CADs

## TECHNICAL SPECIFICATIONS

### TECHNOLOGY

Textile inkjet printing with VSDT Micro Piezo 4 chips per head  
PrecisionCore head technology

### PRINTING

Number of print heads 8, upgradable to 16 heads at the factory  
Compatible inks Epson Genesta inks Acid - Reactive - Disperse - Pigment  
Ink system Closed system with degassed ink bag sizes 3 L as standard or 10 L optional  
Print resolution Range from 300 dpi to 1200 dpi horizontal resolution at 600 dpi or 1200 dpi vertical resolution (1-8 passes)

### BELT

Printing width (cm) 180 - 220\* \* Based upon customer's needs  
Max printing length Unlimited  
Fabric drive Endless belt  
Adhesive type Permanent  
Belt Washing Automatic  
Fabric thickness Up to 10 mm (max height of print heads 12 mm)

### ENVIRONMENTAL CONDITIONS

Operating temperature Temperature: 20°C to 30°C (68°F to 86°F)  
Humidity From 35% to 80% RH (no condensation)  
Recommended printing environment Temperature: 22°C to 28°C (71.6°F to 82.4°F)  
Recommended storage environment Store the printer filled with ink.  
Temperature: 0°C to 40°C (32°F to 104°F)  
1 month, must not be any condensation  
Operating environment Traditional place dust proof

### SIZE & WEIGHT (180 CM 8 HEADS MODEL)

Device size Printer:  
4,610 (W) x 2,040 (D) x 2,070 (H) mm (181x80x81 in)  
Main electric box:  
700 (W) x 1,800 (D) x 2,350 (H) mm (28x71x93 in)  
Optional 10 L ink rack:  
1,240 (W) x 1,300 (D) x 1,220 (H) mm (49x51x48 in)  
Equipment weight Printer: approx. 3,700 kg (8,157 lb)  
Main electric box: approx. 570 kg (1,257 lb)  
Optional 10 L ink rack: approx. 380 kg (838 lb)

### POWER

Voltage 400 V ± 10%, 3-phase + Neutral + Earth  
Frequency 50-60 Hz  
Power consumption 19.5 kW

### COMPRESSED AIR

Compressed air supply Min. 6 bar  
Air supply quality Standard ISO 8573.1 - Class 2, 4, 3  
Air consumption Max. 316 L/h

### WATER

Water pressure Min. 4 bar max 5 bar  
Water flow rate Max. 100 litres per hour

### PRODUCTIVITY

Printing width 1,500 mm  
Printing mode Bidirectional  
Dot size Variable  
Maximum printing speed Up to 234 sqm/h (156 Lmt/h) (300x600 dpi, 1 pass)  
Typical printing speed 125 sqm/h (83 Lmt/h) (600x600 dpi, 2 pass)  
86 sqm/h (57 Lmt/h) (900x600 dpi, 3 pass)

## Supplies

- **Acid**  
Black, Cyan, Magenta, Yellow, Red, Blue, Orange, Cobalt, Grey, Rubine, Fluorescent Flavine, Fluorescent Pink, Across (Ink Penetration Liquid)
- **Reactive**  
Black, Cyan, Magenta, Yellow, Red, Blue, Orange, Grey, Crimson, Across (Ink Penetration Liquid)
- **Disperse**  
Black, Cyan, Magenta, Yellow, Red, Blue, Orange, Grey
- **Pigment**  
Black, Cyan, Magenta, Yellow, Red, Green, Orange, Grey

## Options

- **Belt washing heater**  
Recommended for 16 heads upgrade
- **Expansion beam 2" (standard) or 3"**
- **2 types of pressure rollers**
  - With rubber coating
  - In aluminium alloyBoth devices can have different weight according to the customer needs

Epson Europe B.V.  
Atlas Gebouw, Hoogoorddreef 5  
1101 BA Amsterdam, The Netherlands

[www.monnalisadtp.eu](http://www.monnalisadtp.eu)

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.  
Product information is subject to change without prior notice.  
Pictures in this document are shown for illustrative purposes only.



**EPSON**<sup>®</sup>